



Mobile workstation Regula 83X3M



The workstation is intended for automated reading and authenticity verification of passports, ID cards, driving licenses, visas and other security documents.

Regula 83X3M enables text and barcode recognition, RFID tag reading.

The function of fingerprint scanning and verification is available.



The mobile workstation comprises a tablet PC and an optical document reader. It can be used both as a desktop solution (powered by the AC mains) and as a portable device (powered by a battery pack).

The document reader allows capturing document images in white, infrared, ultraviolet and white coaxial light depending on the workstation model. Regula 83X3M is optionally equipped with an RFID-reader. Workstation operation is controlled via special software **Regula Document Reader SDK**.

Functionality

- Capturing and processing images
 - supported document formats
 - ID-1
 - ID-2
 - ID-3
 - other documents with maximum size 90×130 mm
 - document detection sensor
 - automatic scanning after document detection
 - compensation of external light hitting during image capture in ultraviolet light (Smart UV)
 - $\circ\,$ automated selection of UV illumination intensity according to the document type
 - search and cropping of a document image from a general image
- the MRZ detection and recognition
- recognition and reading of 1D and 2D barcodes
- automated recognition of a document type
- processing graphic fields
- OCR of the visual zone
- reading RFID-tags
- analyzing and comparing text data
- · automated authenticity verification of a document

Operation

- 1. The optical reader automatically detects a document in the reader slot.
- 2. Images of the document in functional illumination modes are formed. At the same time data from an RFID tag is read out.
- 3. A fingerprint is scanned.
- 4. Obtained data are processed by Regula Document Reader SDK.
- 5. The results of processing are available for further use.

Application

- Border control services
- Aviation security services
- Law-enforcement agencies
- Immigration services
- Financial institutions
- Hotels
- Car rental and leasing companies
- Cellular companies
- Business centers security service
- Event-agencies
- Medical institutions
- Tourist agencies
- Ticket offices
- Visa support agencies and consulates
- Insurance companies



Casino security service

Delivery Set

Regula Document Reader SDK



Functionality		Model								
		8303M. 100	8303M. 110	8303M. 111	8323M. 100	8323M. 110	8323M. 111	8333M. 100	8333M. 110	8333M. 111
Light sources of the optical d ocument reader	white	+	+	+	+	+	+	+	+	+
	infrared 870±20 nm	+	+	+	+	+	+	+	+	+
	ultraviolet 365±5 nm		+	+		+	+		+	+
	coaxial white			+			+			+
Biometric fingerprint scanner								+	+	+
RFID-reader					+	+	+	+	+	+

Optical document reader

- Field of view, mm 90×130: full passport page
- Sensor:
 - type CMOS
 - colour model RGB
 - \circ colour depth, bit 24
 - $\circ\,$ megapixels 3
 - $\circ\,$ resolution, ppi 400
 - frame size, pixels 2048×1536

RFID-reader for Regula 8323M.XXX, 8333M.XXX

- Supported standards ISO 14443: RFID tags of type A and B
- PC/SC protocol support
- Data exchange rate, Kbaud 106, 212, 424, 848
- Reading an RFID tag regardless of its position in a document
- Anti-collision: reading an RFID tag according to the MRZ

Biometric fingerprint scanner for Regula 8333M.XXX

- Scanning time, s 0,15
- Size of a window for scanning a fingerprint, mm 16×24
- Resolution, dpi 508
- Frame size, pixels 480×320
- Connection interface USB 2.0

Tablet PC

- CPU Intel® Z8300™ 1.44 GHz
- RAM, Gb 4
- Storage, Gb 64 SSD
- Display 8 inch, IPS, 1280×800 (multi-touch screen)
- Camera 2 MP (front), 5 MP (rear)
- microSD support of up to 256 Gb
- Interfaces 2xUSB 2.0, HDMI, microSIM, Bluetooth 4.0, WiFi 802.11 a/b/g/n, WCDMA (900/2100MHz), HSDPA, GPS/GLONASS/QZSS
- Battery, mAh 8300/3.7V

Regula Iorensic science systems

- Protection rating IP67
- OS Microsoft Windows 10 Pro, 64 bit

Technical specifications

- Dimensions (length×width×height with the PC in the closed position), mm 275×185×151
- Weight, kg, max 4
- Power consumption, W, max 60
- Power supply:
 - $\,\circ\,$ from the AC mains using the power adapter 100—240 V / 19 V
 - from the batteries 4500 mAh / 14,4 V (reader battery pack), 8300 mAh / 3,7 V (PC battery)
- Time of autonomous operation, h, max 6
- Workstation warm-up time, min, not more than 2
- Protection rating IP41
- Connection interfaces 1xUSB 2.0, 1xRJ45 Ethernet 10/100, DC IN 19V
- Additional functions keyboard backlight, torch



Document reader software development kit (SDK)

SDK (Full) consists of three modules:

- Basic supplied together with a device by default
- VizOCR reading textual fields from a document page
- AAC automatic authenticity control

VizOCR and AAC modules are optional and used to extend the functionality of Basic module.

Updates for SDK are provided regularly. Basic module has unlimited support. VizOCR and AAC are updated on subscription basis.

Functionality			Full SDK modules		
		Basic (supplied by default)	VizOCR	AAC	
Doc					
Document formats	 ID-1 (identity card) ID-2 (passport card, visa) ID-3 (passport) other document formats up to 90×130 mm 	+			
Scanning process	 document detection sensor automatic scanning after document detection elimination of glare from laminate and holograms for white and infrared illumination compensation of external light hitting during image capture in UV light (Smart UV) automatic intensity selection of UV illumination for a certain document type search and cropping of a document image from a received image 	+			
	Machine readable zone (MRZ)				
Supported MRZ formats	 in conformity with ICAO 9303: 44×2 30×3 36×2 in conformity with ISO IEC 18013 (IDL): 30×1 support of special MRZ data structure for documents of certain countries 	+			
Features	 search for the MRZ along the whole document image MRZ recognition in infrared and white light control of check digits and data structure in conformity with the requirements of ICAO 9303 and BSI TR-03105 Part 5.1 evaluation of MRZ quality specifications in conformity with ICAO 9303, ISO 7501, 1831, 1073-2 standards 	+			
Barcodes					
Supported formats	 1D: Codabar, Code39 (+extended), Code93, Code128, EAN-8, EAN-13, IATA 2 of 5 (Airline), Interleaved 2 of 5 (ITF), Matrix 2 of 5, STF (Industrial), UPC-A, UPC-E 	+			



	• 2D: PDF417, Aztec Code, QR Code, Datamatrix			
Authentication	barcode format check			+
Au				
Order of document type recognition	 Country→Type→Series 		+	+
Features	 receiving a document template from the SDK database containing the following information: text and graphic fields position availability of barcodes and security features authenticity verification and its parameters RFID-chip availability a reference image from Information Reference Systems «Passport», «Autodocs», «Frontline Documents System» processing of the received document images in compliance with the sample, including document image rotation by the angle given in the sample 		+	+
	Graphic fields processing			
Types of graphic fields	 portrait of the document holder signature barcode fingerprint, etc. 	+		
Features	 cropping and displaying graphic fields as separate images in compliance with the sample of the corresponding document automatic searching of faces on the document image and cropping the document holder portrait if the document type is not recognized document image rotation according to the document holder portrait position 	+		
Recognition of character sets	 Central European and Eastern European Latin (1250) Cyrillic (1251) Western European Latin (1252) Greek (1253) Turkish (1254) Baltic (1257) other fonts of any size 		+	
Features	 dictionary support (name, surname, address, country, etc.) automatic text division into separate fields (e.g. dividing the address into postal code, country, state, etc.) recognition of dates with complex formats recognition of characters from different character sets in one line 		+	
	RFID SDK			
Supported RFID-chip standards	 ISO/IEC 14443-2 (type A and B) ISO/IEC 14443-3 (MIFARE® Classic Protocol) ISO/IEC 14443-4 	+		
Data access modes	DirectBACEAC	+		



			\sim	
	PACE SAC			
Authentication	 active (AA) passive (PA) chip (CA v1, CA v2) terminal (TA v1, TA v2) 	+		
Supported applications	 ePassport (DG1-DG16) eID (DG1-DG21) eSign eDL (DG1-DG14) 	+		
Certificate management	 local storage receiving certificates online through the program interface Master List, CRL support 	+		
Features	 reading RFID chips with extended length support reading RFID chips in compliance with ICAO LDS 1.7, PKI 1.1 data formats certified by BSI TR-03105 Part 5.1, BSI TR-03105 Part 5.2 	+		
A	nalysis and comparison of text data			
Document areas for cross-checking of the readout data	 MRZ VIZ RFID-chip barcode 	+		
Verification	 validity of any dates authenticity of names and surnames according to lists of wordstops zero numbers of sample documents 	+		
Adjustment of formats and measuring units to those used in the user OS	 date weight height, etc. 	+		
Features	 complete or partial comparison of fields integration of data received from several document pages calculated field support (age, etc.) transliteration to Latin characters in compliance with ICAO 9303 standards for comparison with the MRZ 	+		
	Authenticity verification			
Operation available for any document	 checking luminescence (UV Dull Paper) of: the form the MRZ area the portrait area checking the MRZ print contrast in compliance with ICAO 9303 (IR B900 Ink) 			+
Operations available after document type recognition	 checking image patterns in white, IR and UV light checking luminescence of UV protection fibers detection of false luminescence checking photo embedding type: printing or attachment checking IR Visibility of: elements of the form text data the photograph (main and additional) 			+



			\sim	
	 detection of holograms (OVD), OVI reading a luminescent text and comparing it with the data obtained from the MRZ and VIZ (OCR Security Text) visualization of IPI (Invisible Personal Information) checking retroreflective protection checking barcode format 			
Features	 checking operations are adjusted to documents with different degrees of wear and tear the choice of checking operations depends on security features available in a questioned document 			+
	Additional SDK functions			
Image formats	 .BMP .JPG .JP2 .PNG .TIF other image formats are possible on request 	+		
Interoperability	 comparison modules: fingerprint images from RFID chip and external fingerprint scanner face images from document data page and/or RFID chip Information Reference Systems «<u>Passport</u>», «<u>Autodocs</u>», «<u>Frontline Documents System</u>» 	*		
OS compatibility	 Windows 7 (x86, x64), Windows 8, Windows 10 	+		
Drivers	Microsoft certified	+		
Features	 simultaneous optical scanning and RFID chip reading firmware upgrade via USB interface (automatic upgrade after installing new SDK version) multilingual interface 	+		
	Software updates			
SDK	twice a year	*		
Document template database	• monthly	*		

* - on request / individual agreement